

Page 1 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.03.2020 / 0008
Replacing version dated / version: 24.05.2019 / 0007
Valid from: 16.03.2020
PDF print date: 16.03.2020
TP-3820-150 Tracer®UV Additive for R 134a Air Conditioners
TP-3820-500 Tracer®UV Additive for R 134a Air Conditioners
TP-3820-0008-EU R-134a/PAG A/C Dye
TP-3820-0016-EU R-134a/PAG A/C Dye
TP-3820-0301-EU R-134a/PAG A/C Dye
TP-3820-Test bottle Tracer®UV Additive for R 134a Air Conditioners
TP-3820-5500 55 Gallons
Tracer®UV Additive for R 134a Air Conditioners

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

TP-3820-150 Tracer®UV Additive for R 134a Air Conditioners
TP-3820-500 Tracer®UV Additive for R 134a Air Conditioners
TP-3820-0008-EU R-134a/PAG A/C Dye
TP-3820-0016-EU R-134a/PAG A/C Dye
TP-3820-0301-EU R-134a/PAG A/C Dye
TP-3820-Test bottle Tracer®UV Additive for R 134a Air Conditioners
TP-3820-5500 55 Gallons
Tracer®UV Additive for R 134a Air Conditioners

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Fluorescent
Leak detector
Paint
Sector of use [SU]:
SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Chemical product category [PC]:
PC24 - Lubricants, greases, release products
PC26 - Paper and board treatment products
Process category [PROC]:
PROC20 - Use of functional fluids in small devices
Article Categories [AC]:
AC 1 - Vehicles
AC 2 - Machinery, mechanical appliances, electrical/electronic articles
Environmental Release Category [ERC]:
ERC 7 - Use of functional fluid at industrial site

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Page 2 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.03.2020 / 0008
Replacing version dated / version: 24.05.2019 / 0007
Valid from: 16.03.2020
PDF print date: 16.03.2020
TP-3820-150 Tracer@UV Additive for R 134a Air Conditioners
TP-3820-500 Tracer@UV Additive for R 134a Air Conditioners
TP-3820-0008-EU R-134a/PAG A/C Dye
TP-3820-0016-EU R-134a/PAG A/C Dye
TP-3820-0301-EU R-134a/PAG A/C Dye
TP-3820-Test bottle Tracer@UV Additive for R 134a Air Conditioners
TP-3820-5500 55 Gallons
Tracer@UV Additive for R 134a Air Conditioners

Dometic Germany GmbH
Hollefeldstr. 63
48282 Emsdetten
Tel.: +49 (0) 2572 879 0
Fax: +49 (0) 2572 879 300
E-Mail: info@dometic-waeco.de
Homepage: www.waeco.com

Dometic UK Ltd Dometic House
The Brewery
GB- DT11 9LS Blandford St Mary, Dorset
Tel.: +44 (0) 0844 626 0133
Fax: +44 (0) 0844 626 0143
E-Mail: automotive@dometic.co.uk
Homepage: www.airconstations.co.uk

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

IRL

National Poisons Information Centre, Beaumont Hospital, Dublin 9, Ireland, Tel.:
+353 (0)1 809 2166 (Public Poisons Info Line, 8am-10pm, 7 days a week)
+353 (0)1 809 2566 (Info for Healthcare Professionals ONLY, 24 h, 7 days a week)

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (CCWA)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Not applicable

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients

Polyalkylene glycols and additives

3.1 Substance

n.a.

Page 3 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.03.2020 / 0008
 Replacing version dated / version: 24.05.2019 / 0007
 Valid from: 16.03.2020
 PDF print date: 16.03.2020
 TP-3820-150 Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-500 Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-0008-EU R-134a/PAG A/C Dye
 TP-3820-0016-EU R-134a/PAG A/C Dye
 TP-3820-0301-EU R-134a/PAG A/C Dye
 TP-3820-Test bottle Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-5500 55 Gallons
 Tracer@UV Additive for R 134a Air Conditioners

3.2 Mixture

---	---
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP	---
CAS	---
content %	---
Classification according to Regulation (EC) 1272/2008 (CLP)	---

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
 Do not induce vomiting. Consult doctor immediately.
 Danger of aspiration.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes
 Skin irritation possible with prolonged contact.

On vapour formation:

Irritation of the respiratory tract
 Irritant to mucosa of the nose and throat

Ingestion of large quantities:

Nausea
 Gastrointestinal disturbances

Liver damage

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

n.c.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO2
 Dry extinguisher

Page 4 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 16.03.2020 / 0008

Replacing version dated / version: 24.05.2019 / 0007

Valid from: 16.03.2020

PDF print date: 16.03.2020

TP-3820-150 Tracer@UV Additive for R 134a Air Conditioners

TP-3820-500 Tracer@UV Additive for R 134a Air Conditioners

TP-3820-0008-EU R-134a/PAG A/C Dye

TP-3820-0016-EU R-134a/PAG A/C Dye

TP-3820-0301-EU R-134a/PAG A/C Dye

TP-3820-Test bottle Tracer@UV Additive for R 134a Air Conditioners

TP-3820-5500 55 Gallons

Tracer@UV Additive for R 134a Air Conditioners

Alcohol resistant foam

Water jet spray

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Fume

Oxides of carbon

Oxides of nitrogen

Toxic pyrolysis products.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Remove possible causes of ignition - do not smoke.

Ensure sufficient supply of air.

Avoid inhalation, and contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent surface and ground-water infiltration, as well as ground penetration.

Prevent from entering drainage system.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid aerosol formation.

Ensure good ventilation.

Do not heat to temperatures close to flash point.

Avoid long lasting or intensive contact with skin.

Do not carry cleaning cloths soaked in product in trouser pockets.

Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.

Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Page 5 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.03.2020 / 0008
 Replacing version dated / version: 24.05.2019 / 0007
 Valid from: 16.03.2020
 PDF print date: 16.03.2020
 TP-3820-150 Tracer®UV Additive for R 134a Air Conditioners
 TP-3820-500 Tracer®UV Additive for R 134a Air Conditioners
 TP-3820-0008-EU R-134a/PAG A/C Dye
 TP-3820-0016-EU R-134a/PAG A/C Dye
 TP-3820-0301-EU R-134a/PAG A/C Dye
 TP-3820-Test bottle Tracer®UV Additive for R 134a Air Conditioners
 TP-3820-5500 55 Gallons
 Tracer®UV Additive for R 134a Air Conditioners

Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Store product closed and only in original packing.
 Not to be stored in gangways or stair wells.
 Protect against moisture and store closed.
 Store cool.
 Protect from direct sunlight and warming.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

GB	Chemical Name	Oil mist, mineral	Content %:
	WEL-TWA: 5 mg/m3 (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---	---
	Monitoring procedures: - Draeger - Oil Mist 1/a (67 33 031)		
	BMGV: ---	Other information: ---	
IRL	Chemical Name	Oil mist, mineral	Content %:
	OELV-8h: 5 mg/m3 (Mineral oil, pure, highly & severely refined (inhalable))	OELV-15min: ---	---
	Monitoring procedures: - Draeger - Oil Mist 1/a (67 33 031)		
	BLV: ---	Other information: ---	

GB WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

IRL OELV-8h = Occupational Exposure Limit Value (8-hour reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). |
 OELV-15min = Occupational Exposure Limit Value (15-minute reference period). (IFV) = Inhalable Fraction and Vapour. (I) = Inhalable Fraction. (R) = Respirable Fraction.
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
 BLV = Biological limit value |

Page 6 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.03.2020 / 0008
Replacing version dated / version: 24.05.2019 / 0007
Valid from: 16.03.2020
PDF print date: 16.03.2020
TP-3820-150 Tracer@UV Additive for R 134a Air Conditioners
TP-3820-500 Tracer@UV Additive for R 134a Air Conditioners
TP-3820-0008-EU R-134a/PAG A/C Dye
TP-3820-0016-EU R-134a/PAG A/C Dye
TP-3820-0301-EU R-134a/PAG A/C Dye
TP-3820-Test bottle Tracer@UV Additive for R 134a Air Conditioners
TP-3820-5500 55 Gallons
Tracer@UV Additive for R 134a Air Conditioners

Other information: Carc1A, Carc1B = carcinogenic substance, Cat. 1A or 1B. Muta1A, Muta1B = mutagenic substance, Cat. 1A or 1B. Repr1A, Repr1B = Substances known to be toxic for reproduction, Cat. 1A or 1B. Sk = can be absorbed through skin. Asphx = asphyxiant. Sen = Respiratory sensitizer. BOELV = Binding Occupational Exposure Limit Values. IOELV = Indicative Occupational Exposure Limit Values.

(13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. BS EN 14042.

BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN 374).

If applicable

Protective nitrile gloves (EN 374).

Minimum layer thickness in mm:

0,35

Permeation time (penetration time) in minutes:

>= 480

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Filter A2 P2 (EN 14387), code colour brown, white

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

If applicable, these are included in the individual protective measures (eye/face protection, skin protection, respiratory protection).

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Page 7 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.03.2020 / 0008
 Replacing version dated / version: 24.05.2019 / 0007
 Valid from: 16.03.2020
 PDF print date: 16.03.2020
 TP-3820-150 Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-500 Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-0008-EU R-134a/PAG A/C Dye
 TP-3820-0016-EU R-134a/PAG A/C Dye
 TP-3820-0301-EU R-134a/PAG A/C Dye
 TP-3820-Test bottle Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-5500 55 Gallons
 Tracer@UV Additive for R 134a Air Conditioners

Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Light brown
Odour:	Mild
Odour threshold:	Not determined
pH-value:	n.a.
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	>200 °C
Flash point:	152 °C (ASTM D 93 (Pensky-Martens, closed cup))
Evaporation rate:	Not determined
Flammability (solid, gas):	Not determined
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	<0,01 mmHg (20°C)
Vapour density (air = 1):	>1
Density:	0,98 g/ml
Bulk density:	Not determined
Solubility(ies):	Not determined
Water solubility:	<0,1 %
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	28-32,6 cSt (40°C)
Explosive properties:	Not determined
Oxidising properties:	Not determined

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

See also Subsection 10.2 to 10.6.
 The product has not been tested.

10.2 Chemical stability

See also Subsection 10.1 to 10.6.
 Stable with proper storage and handling.

Page 8 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.03.2020 / 0008
 Replacing version dated / version: 24.05.2019 / 0007
 Valid from: 16.03.2020
 PDF print date: 16.03.2020
 TP-3820-150 Tracer®UV Additive for R 134a Air Conditioners
 TP-3820-500 Tracer®UV Additive for R 134a Air Conditioners
 TP-3820-0008-EU R-134a/PAG A/C Dye
 TP-3820-0016-EU R-134a/PAG A/C Dye
 TP-3820-0301-EU R-134a/PAG A/C Dye
 TP-3820-Test bottle Tracer®UV Additive for R 134a Air Conditioners
 TP-3820-5500 55 Gallons
 Tracer®UV Additive for R 134a Air Conditioners

10.3 Possibility of hazardous reactions

See also Subsection 10.1 to 10.6.
 No decomposition if used as intended.

10.4 Conditions to avoid

See also section 7.
 Strong heat

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.
 Reducing agent

10.6 Hazardous decomposition products

See also Subsection 10.1 to 10.5.
 See also section 5.2
 No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

TP-3820-150 Tracer®UV Additive for R 134a Air Conditioners
 TP-3820-500 Tracer®UV Additive for R 134a Air Conditioners
 TP-3820-0008-EU R-134a/PAG A/C Dye
 TP-3820-0016-EU R-134a/PAG A/C Dye
 TP-3820-0301-EU R-134a/PAG A/C Dye
 TP-3820-Test bottle Tracer®UV Additive for R 134a Air Conditioners
 TP-3820-5500 55 Gallons
 Tracer®UV Additive for R 134a Air Conditioners

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.
Other information:						Classification according to calculation procedure.

Page 9 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.03.2020 / 0008
 Replacing version dated / version: 24.05.2019 / 0007
 Valid from: 16.03.2020
 PDF print date: 16.03.2020
 TP-3820-150 Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-500 Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-0008-EU R-134a/PAG A/C Dye
 TP-3820-0016-EU R-134a/PAG A/C Dye
 TP-3820-0301-EU R-134a/PAG A/C Dye
 TP-3820-Test bottle Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-5500 55 Gallons
 Tracer@UV Additive for R 134a Air Conditioners

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

TP-3820-150 Tracer@UV Additive for R 134a Air Conditioners
TP-3820-500 Tracer@UV Additive for R 134a Air Conditioners
TP-3820-0008-EU R-134a/PAG A/C Dye
TP-3820-0016-EU R-134a/PAG A/C Dye
TP-3820-0301-EU R-134a/PAG A/C Dye
TP-3820-Test bottle Tracer@UV Additive for R 134a Air Conditioners
TP-3820-5500 55 Gallons
Tracer@UV Additive for R 134a Air Conditioners

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Mechanical precipitation possible.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

07 03 04 other organic solvents, washing liquids and mother liquors

07 03 08 other still bottoms and reaction residues

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

E.g. suitable incineration plant.

For contaminated packing material

Pay attention to local and national official regulations.

Empty container completely.

Uncontaminated packaging can be recycled.

Dispose of packaging that cannot be cleaned in the same manner as the substance.

15 01 01 paper and cardboard packaging

15 01 02 plastic packaging

15 01 04 metallic packaging

SECTION 14: Transport information

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 16.03.2020 / 0008
 Replacing version dated / version: 24.05.2019 / 0007
 Valid from: 16.03.2020
 PDF print date: 16.03.2020
 TP-3820-150 Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-500 Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-0008-EU R-134a/PAG A/C Dye
 TP-3820-0016-EU R-134a/PAG A/C Dye
 TP-3820-0301-EU R-134a/PAG A/C Dye
 TP-3820-Test bottle Tracer@UV Additive for R 134a Air Conditioners
 TP-3820-5500 55 Gallons
 Tracer@UV Additive for R 134a Air Conditioners

General statements

14.1. UN number: n.a.
Transport by road/by rail (ADR/RID)
 14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 Classification code: n.a.
 LQ: n.a.
 14.5. Environmental hazards: Not applicable
 Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 Marine Pollutant: n.a.
 14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:
 14.3. Transport hazard class(es): n.a.
 14.4. Packing group: n.a.
 14.5. Environmental hazards: Not applicable

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 General hygiene measures for the handling of chemicals are applicable.

Directive 2010/75/EU (VOC): 0 %

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 1

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

Page 11 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.03.2020 / 0008
Replacing version dated / version: 24.05.2019 / 0007
Valid from: 16.03.2020
PDF print date: 16.03.2020
TP-3820-150 Tracer@UV Additive for R 134a Air Conditioners
TP-3820-500 Tracer@UV Additive for R 134a Air Conditioners
TP-3820-0008-EU R-134a/PAG A/C Dye
TP-3820-0016-EU R-134a/PAG A/C Dye
TP-3820-0301-EU R-134a/PAG A/C Dye
TP-3820-Test bottle Tracer@UV Additive for R 134a Air Conditioners
TP-3820-5500 55 Gallons
Tracer@UV Additive for R 134a Air Conditioners

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
AOX Adsorbable organic halogen compounds
approx. approximately
Art., Art. no. Article number
ASTM ASTM International (American Society for Testing and Materials)
BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)
BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
BSEF The International Bromine Council
bw body weight
CAS Chemical Abstracts Service
CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR carcinogenic, mutagenic, reproductive toxic
DMEL Derived Minimum Effect Level
DNEL Derived No Effect Level
dw dry weight
e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
EC European Community
ECHA European Chemicals Agency
EEC European Economic Community
EINECS European Inventory of Existing Commercial Chemical Substances
ELINCS European List of Notified Chemical Substances
EN European Norms
EPA United States Environmental Protection Agency (United States of America)
etc. et cetera
EU European Union
EVAL Ethylene-vinyl alcohol copolymer
Fax. Fax number
gen. general
GHS Globally Harmonized System of Classification and Labelling of Chemicals
GWP Global warming potential
IARC International Agency for Research on Cancer
IATA International Air Transport Association
IBC (Code) International Bulk Chemical (Code)
IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCLID International Uniform Chemical Information Database
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
OECD Organisation for Economic Co-operation and Development
org. organic
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration

Page 12 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 16.03.2020 / 0008
Replacing version dated / version: 24.05.2019 / 0007
Valid from: 16.03.2020
PDF print date: 16.03.2020
TP-3820-150 Tracer@UV Additive for R 134a Air Conditioners
TP-3820-500 Tracer@UV Additive for R 134a Air Conditioners
TP-3820-0008-EU R-134a/PAG A/C Dye
TP-3820-0016-EU R-134a/PAG A/C Dye
TP-3820-0301-EU R-134a/PAG A/C Dye
TP-3820-Test bottle Tracer@UV Additive for R 134a Air Conditioners
TP-3820-5500 55 Gallons
Tracer@UV Additive for R 134a Air Conditioners

ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative
wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.